


Product **M16 IP40 female panel mount connector, Contacts: 5 (stereo), Shielding is not possible, dip-solder, IP40**
 Area **M16 IP40 series 680**
 Article number **09 0320 90 05**


Illustration



Ritning



Polbild



	X	Y
1	-3,50	0,00
2	0,00	3,50
3	3,50	0,00
4	-2,47	2,47
5	2,47	2,47

You can find the assembly instruction on the next page.

Technical data

General features

Kontaktdesign female panel mount connector
 Kontaktdonslåsning screw
 Anslutning dip-solder
 Övre gränstemperatur 85 °C
 Lägre gränstemperatur - 40 °C
 Customs tariff number 85369010

Electrical parameters

Märkström (40°C) 6 A
 Märkspänning 60 V
 Märkstötspänning 500 V
 Föroreningsgrad 1
 Överspanningskategori I
 Isoleringsmaterialgrupp III
 Resistans ≤ 5 mΩ
 Insulation resistance ≥ 10¹⁰ Ω
 EMV-behörighet Shielding is not possible
 Kapslingsklass IP40
 Mekanisk livslängd > 500 Mating cycles

Material

Kontaktmaterial CuSn (bronze)
 Kontaktplätering Ag (silver)
 Kontaktkroppsmaterial PBT (UL 94 V-0)
 Kontakthusmaterial Zinc die-cast nickel-plated

Product **M16 IP40 female panel mount connector, Contacts: 5 (stereo), Shielding is not possible, dip-solder, IP40**

Area **M16 IP40 series 680**
Article number **09 0320 90 05**

Installationsinstruktioner / Monteringsutdrag



Product	M16 IP40 female panel mount connector, Contacts: 5 (stereo), Shielding is not possible, dip-solder, IP40
Area	M16 IP40 series 680
Article number	09 0320 90 05

Security notices

The connectors are designed for use in plant, control system and electrical equipment. The end user is responsible for checking whether the connectors are suitable for use in other applications.